

# GLE/RMVC-300Hv3 - GLE/RMVC-300Hv3-LV

## High Definition - Rugged Miniature Video Camera

### Main Features

- 2 Megapixels (1,920 x 1,080 resolution @ 60 fps)
- 1/2.8" Progressive Scan CMOS, active-pixel, sensor array
- Output: HD-SDI
- Low latency image processing DSP based
- Lens - standard or rugged C-mount
- Setup and control via RS232 or RS485
- Setup software GUI for all camera functions
- Miniature / Hi-G construction to meet MIL STD specs
- Anti-reflective black anodized enclosure
- Wide operating temperature range
- Extended DC voltage supply range

### Applications

- Flight / Vehicle Testing
- Stores / Payloads separation
- Icing and De-icing of Aircraft / Vehicle parts
- Head-Up / Cockpit Display
- Aircraft / UAV / Vehicle Monitoring
- Video surveillance in Harsh Environments

### Overview

**GLE/RMVC-300Hv3 (-LV)** is a miniature and rugged, high-definition (HD) color video camera, designed for on board and in harsh environments testing and instrumentation applications. It is based on a well-proven high quality 1/2.8" Progressive Scan CMOS Sensor, housed in a solid and EMI shielded, precisely machined aluminum enclosure. A low latency powerful DSP dynamically adjusts the settings for a perfect color balance while providing great image accuracy by removing saturation artifacts.

A wide family of standard or rugged, C mount lenses allows the right matching to any field of view. Thanks to the provided software-GUI, via a standard RS 232 serial interface, it is easy to setup all the functions, as frame rate, shutter speed, white balance, backlight compensation, wide dynamic range, gain level, noise reduction. It provides a HD-SDI video output on a robust coaxial connector. GLE/RMVC-300Hv3 (-LV) has been designed to meet MIL-STD specs; the result is a very small, lightweight and at the same time an

exceptionally robust unit that can be easily and safely used in the most demanding applications; installed, directly or with the available optional flanges, in any condition and even where space is at a premium. Its design ensures safe operation, great performances and a high image quality, under extreme environment and in high-vibration conditions, in dust and wet situations, in an extended temperature range and with a wide input DC voltage supply range.



*Due to continuous developments, specifications are subject to change without prior notice. This product is not intended for applications whose its failure to perform can be expected to cause damages to properties and/or persons and/or injury to human life.*

GreenLake Engineering Srl  
the engineering branch of Instrumentation Devices  
Via Acquanera, 29 - 22100 COMO - Italy  
+39.031.521.076 - info@greenlake-eng.com



The other 3 pages of this datasheet are not available on-line.  
To download the full datasheet you need to register at:

**[www.greenlake-eng.com](http://www.greenlake-eng.com)**



*Due to continuous developments, specifications are subject to change without prior notice. This product is not intended for applications whose its failure to perform can be expected to cause damages to properties and/or persons and/or injury to human life.*

GreenLake Engineering Srl  
the engineering branch of Instrumentation Devices  
Via Acquanera, 29 - 22100 COMO - Italy  
+39.031.521.076 - info@greenlake-eng.com

